

Corrigendum

Date: -14/04/2017

NAME OF WORK: a) Renovation of washrooms in HAHC Hospital.
Estimated amount Rs.30,82,656
d) Repair of washrooms in HAHC Hospital.
Estimated amount Rs.10,45,529

Subject: - Corrigendum for short term Tender/ Quotation Notice Ref. No. JH/MS/2017/A-5

Dated 4/04/2017

This is in reference of Short Term Tender/ Quotation Notice Ref. No. JH/MS/2017/A-5 dated 04/04/2017. Kindly read below mentioned schedule of quantity (Schedule "A" & Schedule "B") for quoting your rates for repair/ renovation work of wash rooms at HAHC Hospital JamiaHamdard.

The contractors may drop the tenders in the tender box placed in the office of the Medical Superintendent, HAHC Hospital, on or before 24-04-17 up to 2.00 p.m.,

Medical Superintendent

HAHC Hospital

Schedule "A"

| Schedule of quantities for petty civil works for Renovation of (13 nos) washrooms in HAHC Hospital at JamiaHamdard | | | | | |
|--|--|------|--------|------|--------|
| G.F. Madicine near ward no 01,05,05 ,First floor near ward no 08,12,14 ,Gynae near ward 22 ,23,Antealed ward no 27,27,28 (obstrict postop ward , Second floor labour staff washroom O.T ,Dr.Dutty Staff washroom 02 nos. | | | | | |
| S.No. | DESCRIPTION OF ITEMS | UNIT | QTY | RATE | AMOUNT |
| 1/15.52 | Dismantling of flushing cistern of all types C.I./PVC/Vitrious China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead. each 354.45 | Each | 40.00 | | |
| 2/15.25 | Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. | Sqm | 324.00 | | |
| 3/15.23 .1 | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm | Sqm | 916.00 | | |
| 4/15.51 | Dismantling of road gully chamber / Nainitrape and P or S trape of various sizes including C.I. grating with frame including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead including refilling the excavated gap. | Each | 44.00 | | |
| 6/15.2. 2 | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) | Cum | 25.00 | | |
| 7/22.5 | Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement ompound consisting of applying : a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/ sqm. This layer will be allowed to air cure for 4 hours. b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours. The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry. | Sqm | 507.00 | | |
| 8/18.76 .1 | Cutting holes up to 30x30 cm in walls including making good the same: With common burnt clay F.P.S. (non modular) bricks | Each | 44.00 | | |
| 9/15.45 .1 | Dismantling C.I. pipes including excavation and refilling trenches after taking out the pipes, manually/ by mechanical means breaking lead caulked joints,melting of lead and making into blocks including stacking of pipes & lead at site within 50 metre lead as per direction of Engineer-in-charge: Up to 150 mm diameter metre . | Mtr | 70.00 | | |
| 10/17.6 0.1 | Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors 100 mm inlet and 100 mm outlet | Each | 44.00 | | |

| | | | | | |
|-------------------|--|-----------|--------|--|--|
| 11/ 4.1.5 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:3:6 (1 Cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) | Cu m | 25.00 | | |
| 12/11 .26.1 | Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) :25 mm thick | Sq m | 324.00 | | |
| 13/11 .36 | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. | Sq m | 916.00 | | |
| 14/17 .1.1 | Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required: White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests | Eac h | 17.00 | | |
| 15/ 17.3. 1 | Providing and fixing white vitreous china pedestal type water closet (European type) with seat and lid, 10 litre low level white vitreous china flushing cistern & C.P. flush bend with fittings & C.I. brackets, 40 mm flush bend, overflow arrangement with specials of standard make and mosquito proof coupling of approved municipal design complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required : W.C. pan with ISI marked white solid plastic seat and lid | Eac h | 11.00 | | |
| 16/18 .8 | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. | | | | |
| a | 15 mm nominal outer dia Pipes | Met re | 90.00 | | |
| b | 20 mm nominal outer dia Pipes | Met re | 50.00 | | |
| c | 25 mm nominal outer dia Pipes | Met re | 35.00 | | |
| d | 32 mm nominal outer dia Pipes | Met re | 10.00 | | |
| 17/4. 1.3 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) | Cu m | 1.00 | | |

| | | | | | |
|-----------------|---|------|------------|--|--|
| 18/5. 22.1 | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level.Mild steel and Medium Tensile steel bars | Kg | 50.00 | | |
| 19/18 .56.2 | Providing and fixing PTMT pillar cock of approved quality and colour 15 mm nominal bore, 125 mm long foam flow, eighing not less than 120 gms | Each | 22.00 | | |
| 20/18 .54.2 | Providing and fixing PTMT bib cock of approved quality and colour 15 mm nominal bore, 122mm long, weighing not less than 99 gms | Each | 16.00 | | |
| 21/18 .54.1 | Providing and fixing PTMT bib cock of approved quality and colour.15mm nominal bore, 86 mm long, weighing not less than 88 gms | Each | 28.00 | | |
| 22/18 .63 | Providing and fixing PTMT angle stop cock 15mm nominal bore,weighing not less than 85gms | Each | 67.00 | | |
| 23/12 .37.1 | Providing and fixing 100 mm diameter and 60 cm long rain water spout in cement mortar 1:4 (1 cement : 4 fine sand). Stone ware spout | Each | 11.00 | | |
| 24/17 .32.4 | Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing : Rectangular shape 1500x450 mm | Sqm | 10.00 | | |
| 24/18 .21.2. | Providing and fixing uplasticised PVC connection pipe with brass unions :45 cm length 15 mm nominal bore | Each | 67.00 | | |
| 25/9. 21.2 | Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws | Sqm | 92.00 | | |
| 26/12 .45 | Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recomme-nded jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with 12.45.2, 12.5 mm thick | Sqm | 324.0 0 | | |

| | | | | | | | | |
|--|---------|------|--------|--------|--|--|--|--|
| | tapered | edge | gypsum | fire.. | | | | |
|--|---------|------|--------|--------|--|--|--|--|

| | | | | | |
|----------------|--|-------|------------|--|--|
| 27/14 .46 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | Sqm | 553.0 0 | | |
| 28/13 .8 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | Sqm | 229.0 0 | | |
| 29/13 .43 | Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface :Water thinnable cement primer | Sqm | 553.0 0 | | |
| 30/13 .41.1 | Distempering with oil bound ashable distemper of approved brand and anufacture to give an even shade : New work (two or more coats) over and including water tinnable priming coat with cement primer | Sqm | 553.0 0 | | |
| 31/14 .54.1 | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : One or more coats on old work | Sqm | 150.0 0 | | |
| 32/14 .1.1 | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete,including disposal of rubbish to the dumping ground within 50 metres lead With cement mortar 1:4 (1 cement : 4 fine sand) | Sqm | 50.00 | | |
| 33/9. 7.7.2 | Providing & fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows, all complete 5.5 mm thick glass panes. | Sqft | 25.00 | | |
| 34/12 .41.1 | Providing and fixing on wall face unplastised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. 75 mm diameter | Metre | 50.00 | | |
| 35/12 .41.2 | 110 mm diameter | Metre | 60.00 | | |
| 36/12 .42 | Providing and fixing on wall face unplastised - PVC moulded fittings/accessories for unplastised Rigid PVC rain water pipes conforming to IS :13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. | | | | |
| 12.42 .3.1 | Single tee with door 75x75x75 mm | Each | 12.00 | | |
| 12.42 .1.2 | Coupler 110 mm | Each | 15.00 | | |
| 12.42 .1.1 | 75 mm | Each | 15.00 | | |

| | | | | | |
|----------------|---|------|-------|--|--|
| 37/12 .43.1 | Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete. 75 mm | Each | 16.00 | | |
| 38/12 .43.2 | 110 mm | Each | 16.00 | | |
| 39/12 .44 | Providing and fixing to the inlet mouth of rain water pipe cast iron grating 15 cm diameter and weighing not less than 440 grams. | Each | 6.00 | | |

| | | | | | |
|-----------|--|------|---------|--|--|
| 40/9.74.1 | Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete :250x10 mm | Each | 30.00 | | |
| 42/9.75.1 | Providing and fixing bright finished brass door latch with necessary screws etc. complete : 300x16x5 mm | Each | 30.00 | | |
| 43/9.83 | Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete. | Each | 11.00 | | |
| 44/9.81.1 | 9.81 Providing and fixing bright finished brass handles with screws etc.complete: 125 mm | Each | 30.00 | | |
| 45 | Removing khanger in sunkon portion | Cft | 5264.00 | | |
| 46 | Refilling khanger in sunkon portion Available | Cft | 5264.00 | | |
| 47 | Providing and laying khanger | Cft | 50.00 | | |
| 48 | Providing and fixing Exhaust fan with louvers .Size of 18" (AS per electrical approved rate) | Each | 13.00 | | |
| 49 | Providing and fixing wiring for the light point /fan point ,exhaust fan point with piano type 2x1.5 sqmm ,pvc insulated copper condutor cable in surface /recessed pvccoundute /casing & capping as required along with 5 amp switch on board comletae in all respect. | Each | 32.00 | | |
| 50 | Supplying and fixing ceillingpannel light 12 watt (phillps,surya,bajaj make) | Each | 32.00 | | |
| | Total Amount of Schedule "A" | | | | |

Total Amount of Schedule "A" (In Words) INR

Schedule "B"

| Schedule of quantities for petty civil repair works of (22 nos) washrooms in HAHC hospital at JamiaHamdard | | | | | |
|--|--|------|-----------|------|--------|
| G.floor staff washrooms, Near Dileiswashroom ,Repseption Area washroom ,Emergency washrooms changing room washrooms ,First floor staff toilet Paeditric washrooms infront of pediatric washrooms ,Second floor gallery washrooms ,ICU area washrooms ,Lbour room female washrooms. | | | | | |
| S.No | DESCRIPTION OF ITEMS | UNIT | QUAN TITY | RATE | AMOUNT |
| 1/15. 52 | Dismantling of flushing cistern of all types .I./PVC/Vitrious China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead. each 354.45 | Each | 20.00 | | |
| 2/15. 25 | Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. | Sqm | 69.59 | | |
| 3/15. 23.1 | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm | Sqm | 196.35 | | |
| 4/15. 51 | Dismantling of road gully chamber / Nainitrape and P or S trape of various sizes including C.I. grating with frame including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead including refilling the excavated gap. | Each | 20.00 | | |
| 5/15. 2.2 | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) | Cum | 3.00 | | |
| 6/15. 45.1 | Dismantling C.I. pipes including excavation and refilling trenches after taking out the pipes, manually/ by mechanical means breaking lead caulked joints,melting of lead and making into blocks including stacking of pipes & lead at site within 50 metre lead as per direction of Engineer-in-charge: Up to 150 mm diameter metre . | Mtr | 80.00 | | |
| 7/18. 76.1 | Cutting holes up to 30x30 cm in walls including making good the same: With common burnt clay F.P.S. (non modular) bricks | Each | 20.00 | | |

| | | | | | |
|------------|--|-----|-------|--|--|
| 8/22. 5 | Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying : a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/sqm. This layer will be allowed to air cure for 4 hours. b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours. The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry. | Sqm | 67.00 | | |
|------------|--|-----|-------|--|--|

| | | | | | |
|----------------|---|------|--------|--|--|
| 9/ 4.1.5 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:3:6 (1 Cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) | Cum | 1.00 | | |
| 10/11 .26.1 | Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) :25 mm thick | Sqm | 70.00 | | |
| 11/11 .4 | Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in all colours, shades, except White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement : 4 Coarse sand), including pointing the joints with white cement and matching pigments etc., complete. | sqm | 45.00 | | |
| 12/11 .36 | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. | Sqm | 200.00 | | |
| 13/17 .18.1 | Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete. 10 litre capacity - White | Each | 20.00 | | |
| 14/17 .60.1 | Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors 100 mm inlet and 100 mm outlet | Each | 20.00 | | |

| | | | | | |
|-------------------|--|------|------|--|--|
| 15/17 .1.1 | Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required: White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests | Each | 6.00 | | |
| 16/ 17.3. 1 | Providing and fixing white vitreous china pedestal type water closet (European type) with seat and lid, 10 litre low level white vitreous china flushing cistern & C.P. flush bend with fittings & C.I. brackets, 40 mm flush bend, overflow arrangement with specials of standard make and mosquito proof coupling of approved municipal design complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required : W.C. pan with ISI marked white solid plastic seat and lid | Each | 5.00 | | |

| | | | | | |
|---------------|--|-------|-------|--|--|
| 17/18 .8 | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. | | | | |
| a | 15 mm nominal outer dia Pipes | Metre | 50.00 | | |
| b | 20 mm nominal outer dia Pipes | Metre | 40.00 | | |
| c | 25 mm nominal outer dia Pipes | Metre | 35.00 | | |
| d | 32 mm nominal outer dia Pipes | Metre | 10.00 | | |
| 18/4. 1.3 | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) | Cum | 1.00 | | |
| 19/5. 22.1 | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Mild steel and Medium Tensile steel bars | Kg | 25.00 | | |
| 20/17 .6.1 | Providing and fixing one piece construction white vitreous china squatting plate with an integral longitudinal flushing pipe, white P.V.C. automatic flushing cistern, with fittings, standard size G.I. / PVC flush pipe for back and front flush with standard spreader pipes with fittings, G.I clamps and C.P. brass coupling complete, including painting of fittings and cutting and making good the walls and floors etc. wherever required : Single squatting plate with 5 litre P.V.C. automatic flushing cistern | Each | 5.00 | | |

| | | | | | |
|----------------|---|------|-------|--|--|
| 21/18 .56.2 | Providing and fixing PTMT pillar cock of approved quality and colour 15 mm nominal bore, 125 mm long foam flow, weighing not less than 120 gms | Each | 35.00 | | |
| 22/18 .54.2 | Providing and fixing PTMT bib cock of approved quality and colour 15 mm nominal bore, 122mm long, weighing not less than 99 gms | Each | 25.00 | | |
| 23/18 .54.1 | Providing and fixing PTMT bib cock of approved quality and colour.15mm nominal bore, 86 mm long, weighing not less than 88 gms | Each | 33.00 | | |
| 24/18 .63 | Providing and fixing PTMT angle stop cock 15mm nominal bore, weighing not less than 85gms | Each | 50.00 | | |
| 25/17 .32.4 | Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing : Rectangular shape 1500x450 mm | Sqm | 5.00 | | |

| | | | | | |
|----------------------|--|------|--------|--|--|
| 26/18 .21.2. 1 | Providing and fixing uplasticised PVC connection pipe with brass unions :45 cm length 15 mm nominal bore | Each | 40.00 | | |
| 27/14 .46 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | Sqm | 348.00 | | |
| 28/13 .8 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | Sqm | 348.00 | | |
| 29/13 .43 | Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface :Water thinnable cement primer | Sqm | 348.00 | | |
| 30/13 .41.1 | Distemping with oil bound ashable distemper of approved brand and anufacture to give an even shade : New work (two or more coats) over and including water thinnable priming coat with cement primer | Sqm | 648.00 | | |
| 31/14 .54.1 | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : One or more coats on old work | Sqm | 167.00 | | |
| 32/14 .1.1 | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete,including disposal of rubbish to the dumping ground within 50 metres lead With cement mortar 1:4 (1 cement : 4 fine sand) | Sqm | 50.00 | | |
| 33/9. 7.7.2 | Providing & fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows, all complete 5.5 mm thick glass panes. | Sqft | 25.00 | | |

| | | | | | |
|----------------|---|-------|-------|--|--|
| 34/12 .41.1 | Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. 75 mm diameter | Metre | 50.00 | | |
| 35/12 .41.2 | 110 mm diameter | Metre | 60.00 | | |
| 36/12 .42 | Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS :13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. | | | | |
| 12.42 .3.1 | Single tee with door 75x75x75 mm | Each | 12.00 | | |
| 12.42 .1.2 | Coupler 110 mm | Each | 15.00 | | |
| 12.42 .1.1 | 75 mm | Each | 15.00 | | |

| | | | | | |
|------------|---|------|--------|--|--|
| 37/12.43.1 | Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete. 75 mm | Each | 16.00 | | |
| 12.43.2 | 110 mm | Each | 16.00 | | |
| 38/12.44 | Providing and fixing to the inlet mouth of rain water pipe cast iron grating 15 cm diameter and weighing not less than 440 grams. | Each | 6.00 | | |
| 39/9.74.1 | Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete :250x10 mm | Each | 15.00 | | |
| 40/9.75.1 | Providing and fixing bright finished brass door latch with necessary screws etc. complete : 300x16x5 mm | Each | 15.00 | | |
| 41/9.83 | Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete. | Each | 7.00 | | |
| 42/9.81.1 | Providing and fixing bright finished brass handles with screws etc.complete: 125 mm | Each | 15.00 | | |
| 43 | Removing khanger in sunkon portion | Cft | 510.00 | | |
| 44 | Refilling khanger in sunkon portion Available | Cft | 510.00 | | |
| 45 | Providing and laying khanger | Cft | 100.00 | | |

| | | | | | |
|----|---|------|--------|--|--|
| 46 | Refixing of available urinal | Each | 2.00 | | |
| 47 | Providing and fixing Exhaust fan with louvers .Size of 18" (AS per electrical approved rate) | Each | 22.00 | | |
| 48 | Providing and fixing wiring for the light point /fan point ,exhaust fan point with piano type 2x1.5 sqmm ,pvc insulated copper condutor cable in surface /recessed pvccoundute /casing & capping as required along with 5 amp switcae in all respect. | Each | 20.00 | | |
| 49 | Removing and refixing of available wash basin fixing on ms angle and RCC counters . | Job | 16.00 | | |
| 50 | Reaparing Grid false ceiling with nesseseryfashner,etc.complete. 2'-0"x2'-0" x12 Nos | Sqft | 140.00 | | |
| 51 | Reaparing gypsum false ceiling with nesseseryfshner, etc. complete. 5'-0"x6'-0" x1 Nos | Sqft | 100.00 | | |
| | | | | | |
| | Total Amount of Schedule "B" | | | | |

Total Amount of Schedule "B" (In Words) INR