

**FINANCIAL BID****Annexure-II**

SN	Description	UOM	Qty	Rate	Amount
1	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	Sqm	625		
2	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.				
		sqm	200		
3	Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour.				
	One coat	Sqm	250		
	Two coat	Sqm	1000		
4	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :				
	Two or more coats on new work	Sqm	250		
5	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.				
	With cement mortar 1:4 (1cement: 4 coarse sand)	Sqm	25		
<b>Sub Total</b>					
<b>Add: GST 18%</b>					
<b>Grand Total</b>					