

FINANCIAL BID

Annexure-I

| DCD | FIVALICIAL DID | | | Annext | 110 1 |
|--------------|--|-------|--------|--------|--------|
| DSR- 2021 | Description | UOM | Qty | Rate | Amount |
| 13.91 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | Sqm | 250.00 | | |
| 13.8 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | • | | | |
| | | sqm | 75.00 | | |
| 13.82 | Wall painting with premium acrylic emulsion paint of interior & exterior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour. | Sqiii | 72.00 | | |
| 13.82.1 | One coat | Sqm | 150.00 | | |
| 13.82.2 | Two coat | Sqm | 500.00 | | |
| 13.61 | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : | | | | |
| 13.61.1 | Two or more coats on new work | Sqm | 25 | | |
| 14.1 | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. | | | | |
| 14.1.2 | With cement mortar 1:4 (1cement: 4 coarse sand) | Sqm | 25 | | |
| Total Amount | | | | | |